

SUPER VERSO

is a latex interior undercoat primer paint.



- Improves coverage
- Evens the absorptive capacity
- Smooths and unifies the substrate
- Easy application with a brush, roller or airless spray

USE:

KLEIB SUPER VERSO is a latex interior undercoat primer paint that evens the absorptive capacity of the working surface and smooths the substrate, thus ensuring a uniform colour of the topcoats. The paint is designed for priming walls and ceilings made of cement mortar, cement and lime mortar, gypsum mortar, gypsum plasterboard, wallpaper, as well as for previously painted surfaces, e.g. for repainting dark colours. It improves adhesion and coverage of emulsion topcoats (dispersion, acrylic, latex); it is recommended, among others, to be used under the following paints: KLEIB PURE WHITE, KLEIB SYMFONIA, KLEIB SUPERNOVA. It creates a matt coat that eliminates unevenness and differences in texture and colour of the substrate. KLEIB SUPER VERSO is easy to apply, has a very low splash rate and ensures good coverage. The paint coat is vapour-permeable, which allows for the walls to breathe. KLEIB SUPER VERSO significantly reduces painting costs as it increases the efficiency and yield of topcoats. It is designed for painting indoor walls and ceilings of residential, office and public utility premises.

WORKING SURFACE PREPARATION:

The working surface should be clean, dry, compact, uniform, free of grease and dust. Repair and fill in any scratches, cracks and gaps. The paint is recommended to be applied on strong, compact working surfaces. The surfaces to be painted should be dusted off thoroughly and then washed with water. Reinforce dusty and highly absorbent surfaces, such as gypsum, with KLEIB G2 deep penetrating primer. Note: It is recommended to apply paint from the same batch (date) of production to a given surface, under the same conditions and in the same fashion.

PREPARATION OF PAINT:

The paint is supplied ready to use. It may not be combined with other materials. After opening, mix thoroughly the contents of the bucket until a smooth uniform consistency is obtained.

INSTRUCTIONS FOR USE:

The undercoat paint should be applied in one coat. When applying the primer coat, the paint can be diluted up to 5% with water. A second coat may be necessary for highly absorbent, porous or non-uniform high-contrast substrates. The paint should be applied at an air and working surface temperature of +10°C to +28°C. Further works on the painted surface can be performed 4 hours after the application of the product. Paint plasters after 6 weeks of curing or after the time indicated by the manufacturer of a particular plaster, finishing plaster, putty. General wall paint technology should be maintained. We recommend using a microfiber paint roller or natural bristle roller with a minimum pile height of 12 mm.

STORAGE AND TRANSPORT:

The paint should be stored and transported in tightly closed buckets in dry conditions and at plus temperatures from +5°C to +28°C, in a place protected from direct sunlight. Protect from overheating. Note: Water-based product. It is permanently damaged when temperatures fall below freezing. Do not leave containers open once they have been started. The compound shelf life is 24 months from the date on the packaging.

TECHNICAL SPECIFICATIONS:

Colour	White
Decorative effect	Matt
Density	approx. 1.4 g/cm ³
Drying time (for a single coat, at approx. +20°C and relative humidity of 50%, with good ventilation)	surface drying – 2 hours application of another coat – 4 hours Lower temperature and/or increased humidity may extend the drying time.
Yield	8-10 m ² /l One coat applied on a smooth, even and properly prepared substrate.
Number of coats	1
Thinner	Woda



net weight	pieces per pallet	consumption
10 l	44	0.10-0.13 l/m one coat applied on a smooth, even and properly prepared substrate