

EN**KLEIB®**
PROFESSIONAL**Wood Line**

ACRYLIC PAINT for façade board imitations

- in colours according to the façade board colour chart
- efficient
- UV-resistant
- exceptional aesthetic qualities

KLEIB AF-10 is part of a complex external thermal insulation system with coat finish (ETICS) under the commercial name KLEIB.

APPLICATION

AF-10 is an acrylic façade paint mainly intended for colouring the surface of reinforced layers made as an imitation of a façade board

BASE PREPARATION

The substrate should be dry, load-bearing and seasoned. Before applying paint, the surface should be primed with KLEIB G1.

PAINT PREPARATION

Paint AF-10 is supplied ready for use. After opening the package, its contents should be stirred to even out the consistency.

HOW TO USE

The paint should be spread with a brush or roller, evenly in a thin layer over the entire surface. Depending on the absorbency and structure of the substrate, the paint can be applied in several layers. Apply each successive coat after the previous one has dried, i.e. after approx. 2-6 hours. Protect the applied surfaces from direct sunlight, rain and strong wind. Clean tools with water immediately after use.

CONSUMPTION

The consumption is approximately 0.1-0.15 kg/m².

STORAGE AND TRANSPORT

Store in tightly closed buckets, in dry conditions, at positive temperatures for up to 24 months from the production date on the packaging.

TECHNICAL DATA

Drying time	up to 6 hours
Substrate and ambient temperature during the work	from +5 °C to +25 °C

AF10	net weight	pieces per pallet	consumption
	1 kg	-	approx. 0.1-0.15 kg/m ²