



EN

KLEIB
PROFESSIONAL

KLEIB A1 ACRYLIC WHITE MULTI-PURPOSE PERFECT FOR USE ON PLASTERBOARD

- after curing, the compound remains permanently flexible
- resistant to weather conditions
- workability up to 5 min.
- setting time approx. 2-3 mm/24h

KLEIB A1 acrylic is a flexible malleable multi-purpose sealant, used for filling cracks, scratches and gaps in masonry and for joining structural and building components. It features good adhesion to typical construction materials, i.e. concrete, plaster, brick, wood, plasterboard. For this reason, it is used for durable, flexible bonding of drywall elements, sealing gaps around doors and windows, repairing wall and ceiling surfaces. Acrylic is virtually odourless and can be used both indoors and outdoors. It is resistant to temperature fluctuations, UV radiation and the effects of moisture. Once fully cured, the acrylic can be painted.

WORKING SURFACE PREPARATION/INSTRUCTIONS FOR USE

Surfaces should be clean, dry, free of dust, dirt and grease. Before use, cut off the end of the cartridge and screw on the applicator by cutting it to the appropriate thickness of the joint. Press out the mixture with a suitable application gun. The applied sealant can be smoothed with a spatula, putty knife or other tool wetted with water. **WARNING:** To avoid confusion, check the suitability of the product for the intended use. The uncured product can be washed off with water. **KEEP OUT OF REACH OF CHILDREN.** Avoid contamination of skin and eyes. **SHELF LIFE:** 12 months from the date of production placed on the packaging.

TECHNICAL SPECIFICATIONS

Outdoor use	Performances (value):
Reaction to fire	Class F
Resistance to flow	≤ 3 mm
Loss of volume	≤ 45%
Durability	pass
Indoor use	Performances (value):
Reaction to fire	Class F
Resistance to flow	≤ 5 mm
Loss of volume	≤ 45%
Mechanical properties (elongation) at break at 23°	≥ 25%
Durability	pass

A1	net weight	consumption
	300 ml	approximately 18 running meters of 4x4 mm joint