



EN

KLEIB A3 MOUNTING ADHESIVE

KLEIB
PROFESSIONAL

- multi-purpose
- instant
- mega-strong
- flexible

KLEIB A3 mounting adhesive is a quick-drying, multi-purpose adhesive characterised by very good adhesion to wood, glass, hard PVC, metals and to most materials used in construction, such as brick, concrete, gypsum. It retains elasticity and flexibility after drying. The joints are resistant to water and temperature fluctuations up to +56°C.

USE

Recommended for fixing panels, sections, wall mouldings, skirting boards, thresholds, stairs, cornices, windowsills, plafonds, stone and ceramic tiles. Thermal resistance: -18°C to +56°C. Minimum application temperature: +10°C.

APPLICATION

Adhesive surfaces should be clean, free of dust, dirt, oil, grease, rust and other substances that weaken adhesion. Glass, glazed surfaces, wood should be degreased with alcohol, extraction naphtha or other solvent. Apply the adhesive in spots or in strips to the material to be glued and spread it thoroughly. Bring the surfaces together and then detach. Wait 5 min, bring the surfaces together again and press firmly. The alignment of the glued material can be corrected only by moving (without detaching) the joined surfaces. Leave the glued materials in contact until the adhesive is fully cured. In the case of bonding non-standard materials, it is advisable to perform preliminary tests. SHELF LIFE: 12 months from the date of production placed on the packaging.

A3	net weight	consumption*
	300 ml	approximately 18 running meters of 4x4 mm joint