

EN

KLEiB®
Passion of Life


SYMFONIA

is a latex paint available in the innovative KLEiB colour system, designed for decorative painting of indoor walls and ceilings.

- Exceptional coverage
- Ecological
- No splash
- Matt



Baza systemu kolorowania
KLEiB

USE:

KLEiB SYMFONIA is a latex paint available in the innovative KLEiB colour system, designed for decorative painting of indoor walls and ceilings. The paint forms coats of high decorative values, characterized by excellent coverage, durability and colour purity. The paint is recommended for cement and lime, concrete, gypsum and gypsum plasterboard substrates (also previously painted with emulsion paints). The paint coat is vapour-permeable, which allows for the walls to breathe, and the right texture means that it does not splash when applied. Light dirt can be washed off thanks to its resistance to wet scrubbing.

WORKING SURFACE PREPARATION:

The working surface should be clean, dry, compact, uniform, free of grease and dust. Repair and fill in any scratches, cracks and gaps. The paint is recommended to be applied on strong, compact substrates. The surfaces to be painted should be dusted off thoroughly and then washed with water. Walls painted with chalk-based paint and flaking working surfaces should be washed, then deep penetrating KLEiB G2 primer should be applied. We recommend priming gypsum plasterboards with KLEiB G1 before painting. It is particularly important to prime board joints and areas partially covered with gypsum mortar, as the use of KLEiB G1 primer equalizes the absorbency of the working surface and prevents streaks when painting. Note: it is recommended to apply paint from the same batch (date) of production to a given surface, under the same conditions and in the same fashion.

PREPARATION OF PAINT:

The paint is supplied ready to use. It may not be combined with other materials. After opening, mix thoroughly the contents of the bucket until a smooth uniform consistency is obtained.

INSTRUCTIONS FOR USE:

The paint should be applied in two coats; before painting grey and dark substrates it is recommended to paint them with white KLEiB SYMFONIA (P base). When applying the first primer coat, KLEiB SYMFONIA paint can be diluted up to 10% with water. Dyed paint should be applied undiluted. The product should be applied at an air and working surface temperature of +5°C to +28°C. Subsequent coats are recommended to be applied after at least 4 hours. Paint plasters after 6 weeks of curing or after the time indicated by the manufacturer of a particular plaster, finishing plaster, putty. General wall paint technology should be maintained. We recommend using a microfiber paint roller or natural bristle roller with a minimum pile height of 12 mm.

STORAGE AND TRANSPORT:

The paint should be stored and transported in tightly closed buckets in dry conditions and at plus temperatures from +5°C to +28°C, away from sources of heat. Protect from overheating. Note: water-based product. It is permanently damaged when temperatures fall below freezing. Do not leave containers open once they have been started. The compound shelf life is 24 months from the date on the packaging. The product is not classified as hazardous under the current ADR Agreement. Covered car transport required.

TECHNICAL SPECIFICATIONS:

| | |
|---|---|
| Colour | colours dyed in the KLEiB system |
| Decorative effect | matt |
| Density | 1.23-1.46 g/cm ³ |
| Scrub resistance | according to PN-C 81914:2002 Type I according to PN-EN 13300:2002 – Class 2 |
| Drying time (for a single coat, at approx. +20°C and relative humidity of 50%, with good ventilation) | surface drying – 2 hours application of another coat – 4 hours Lower temperature and/ or increased humidity may extend the drying time. |
| Number of coats | 2 |
| Thinner | water |



| net weight | pieces per pallet | consumption |
|------------|-------------------|---|
| 5 l | 90 | 0.08-0.10 l/m ² (one coat applied on a smooth, even and properly prepared substrate) |
| 10 l | 33 | |